

Enermax FP70TSX

Specifications

MODEL	FP70TSX
SERIES	ENERMAX
GENERATOR SPECS	
PRIME (kW)	56.0
STANDBY (kW)	61.5
RPM	1800
VOLTAGE 1PH	240/120V
VOLTAGE 3PH	480/277V
	208/120V
FREQUENCY (Hz)	60
CONTROLLER BRAND	Deep Sea
CONTROLLER MODEL	DSE7310
ALTERNATOR MAKE	Leroy Somer
ALTERNATOR MODEL	LSA 44.3S2
SYSTEM VOLTAGE	24V
SOUND LEVEL @ 23 FEET	69
AMPS	
SINGLE PHASE 120V zz	192 X 2 zz
SINGLE PHASE 240V	192
THREE PHASE 208V	194
THREE PHASE 240V	168
THREE PHASE 480V	84
ENGINE SPECS	
MAKE	FPT
MODEL	NEF45SM2X
EPA LEVEL	Tier 3 Flex
No. Cylinders	4
HP	90
EXTERNAL FUEL VALVE	YES
FUEL CONTAINMENT	110%
FUEL CONSUMPTION	
FUEL CAPACITY (Gallons)	92
80%	3.6g/h
RUN TIME @ 80%	26hrs
WEIGHTS AND DIMENSIONS	
SKID W/O TRAILER	
WEIGHT wet (lbs.)	4012
LENGTH (in.)	100
WIDTH (in.)	46
HEIGHT (in.)	69
* The weights and dimensions ma	av he subject

to change. Please refer to the technical drawing.

Features & Benefits

TecnoGen's FP70TSX generator is powered by a FPT diesel engine coupled to an industry standard Leroy Somer alternator provides 56 kW of prime power.

Features internal fuel capacity of 92 gallons giving you 26 hours of run time @ 80% load. A DeepSea controller makes retrieving vital stats like fuel levels, run time and start logs easy. Sealed doors and 2" thick insulation throughout allow for a 69 dBA rating.



- 1. Courtesy outlets available in all phases at proper voltage
- 2. Sealed doors and 2" thick insulation throughout
- 3. Fork pockets
- 4. Available in skid or trailer mounted version



Engine

An FPT NEF45SM2X diesel engine provides quiet and efficient power while not requiring a costly DPF.



Control Panel

Control panel, with Deep Sea Controller, laid out and labeled for easy use.



Camlocks

Camlocks are standard in addition to the lugs for easy color coded hook ups when using distribution panels and boxes.

Main status and Four configurable LEDs instrumentation display Engage breaker (in parallel option) Menu navigation buttons Open generator Mute alarm/lamp test (in parallel option) Start engine t . . Select stop mode (when in manual mode) Select manual mode Select auto mode

FTE

FTG Equipment Solutions, Inc., 399 N Virginia Ave., Carney's Point, NJ 08069

Toll Free (855) 303-7900 / Fax (856) 351-9352 / sales@ftgequipment.com / www.ftgequipment.com

Deep Sea Controller